

# Steel Rolling Warehouse Ladder 58 Degree 8 Grip Strut 23-9/16 In. Step Width 350 Lb. Capacity Blue

**MODEL LAD-8-14-G**

Industrial Ladders / Rolling Warehouse Ladders (6-11 Step)



## PRODUCT OVERVIEW

The warehouse ladders are a great addition to the material handling and shipping facilities. The strong welded construction is powder coated for a sleek reliable finish that will stay durable throughout daily use. The ladder construction promotes safety through a bottom yellow step that indicates the end of the unit. The unit can be locked in place by pressing the levers below the bottom step. Once levers are engaged the ladder cannot be moved. A resilient handrail offers stability while climbing and exiting the ladders.

## KEY FEATURES

- Steel construction for lasting durability
- Grip Strut steps for safe traversing
- Rolling design for maneuvering in condensed areas
- Bottom step is colored yellow for utmost safety

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**196 lbs**

**ASSEMBLED SIZE**  
**34.25" W x 66.9375" L x 110" H**

**SHIP WEIGHT**  
**288 lbs**

**PACKAGE 1 SIZE**  
**40" W x 132" D x 22" H**

**COLOR / FINISH**  
**Blue**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                                  |              |
|--------------------------------------------------|--------------|
| Uniform Capacity (lb.)                           | 350          |
| Number of Steps (qty.)                           | 8            |
| Step Angle (degrees)                             | 58           |
| Top Step Height (in.)                            | 80           |
| Top Step Depth (in.)                             | 14           |
| Step Depth (in.)                                 | 7            |
| Usable Width (in.)                               | 23-9/16      |
| Usable Length (in.)                              | 57-3/4       |
| Step Type                                        | Grip Strut   |
| Step Spacing (in.)                               | 10           |
| Front Swivel Poly Caster Quantity/Diameter/Width | (2) 3x1-1/4  |
| Rear Rigid Hard Rubber Caster Quantity/Diameter  | (2) 10x2-1/2 |
| OSHA                                             | 1910.29      |
| ANSI                                             | A14.7        |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=602>