

# Steel Adjustable Spreader Beam 78 In. Length 2,500 Lb. Capacity Blue

**MODEL SBM-25**

Overhead Lifting / Adjustable Spreader Beams

## PRODUCT OVERVIEW

The adjustable spreader beam is ideal for the manufacturing and maintenance facilities. The steel construction keeps the unit durable and strong for a lifetime of use. The beam is shipped with a test certificate.

## KEY FEATURES

- Designed to lift and move uneven and awkward loads
- Complies with ASME B30.20-1993 standards
- Includes two lower bails and one upper bail standard for added versatility
- Welded steel construction for heavy duty performance

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**119 lbs**

**ASSEMBLED SIZE**  
**5" W x 78" L x 16.5" H**

**SHIP WEIGHT**  
**178 lbs**

**PACKAGE 1 SIZE**  
**29" W x 92" D x 10" H**

**COLOR / FINISH**  
**Blue**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Out of Stock - Please Contact Sales

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                      |               |
|--------------------------------------|---------------|
| Uniform Capacity (lb.)               | 2,500         |
| Headroom (in.)                       | 14-3/4        |
| Minimum Spread (in.)                 | 8             |
| Maximum Spread (ft.)                 | 6             |
| Usable Upper Bail Width/Height (in)  | 2-1/2 x 4-1/2 |
| Usable Lower Bail Width/Height (in.) | 1-1/2 x 4-1/2 |
| Upper/Lower Bail Thickness (in.)     | 3/4           |
| ASME                                 | B30.20-1993   |
| C-Channel Height (in.)               | 5             |
| Overall Width (in.)                  | 5             |
| Overall Height (in.)                 | 16-1/2        |
| Overall Length (in.)                 | 78            |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=572>