

# Galvanized Steel AC Powered Jib Crane 4-7 Ft. Boom 2,000 Lb. Capacity Gray

**MODEL WTJ-20-4-AC-GAL**

Overhead Lifting / Power Lift Jib Cranes

## PRODUCT OVERVIEW

The Jib crane is ideal for lifting objects in a variety of areas. With a steel construction and a galvanized finish, the jib crane also features a telescopic boom with an adjustable length and height, manual boom rotation, powered cable winch for easy lifting and maneuvering, and a fingertip switch control. Unit is designed for vertical lifting only. Do not use unit for lifting personnel or overhead lifting.

## KEY FEATURES

- Powered cable winch makes lifting and maneuvering easy
- Boom telescopes in and out for greater reach and versatility
- 360 Degrees swivel design allows for maximum accessibility
- Pre-drilled base plate makes mounting quick and easy

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**259 lbs**

**ASSEMBLED SIZE**  
**12" W x 65.375" L x 70.0625" H**

**SHIP WEIGHT**  
**294 lbs**

**PACKAGE 1 SIZE**  
**29" W x 67" D x 18" H**

**COLOR / FINISH**  
**Gray**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                            |                   |
|--------------------------------------------|-------------------|
| Uniform Capacity (lb.)                     | 2,000             |
| Boom Reach (in.)                           | 51-1/4 to 87-1/4  |
| Boom Height (in.)                          | 59-1/2 to 106-1/2 |
| Rotation Degree                            | 360               |
| Boom Adjustment Increments (in.)           | 12                |
| Cable Length (ft.)                         | 25                |
| Cable Diameter (in.)                       | 7/32              |
| AC (volts)                                 | 120               |
| Horsepower (HP)                            | 1/3               |
| Mounting Plate Length (in.)                | 12                |
| Mounting Plate Width (in.)                 | 12                |
| Capacity at 59-1/2" Fully Retracted (lbs.) | 1,100             |
| Capacity at 59-1/2" Second Position (lbs.) | 800               |
| Capacity at 59-1/2" Third Position (lbs.)  | 600               |
| Capacity at 59-1/2" Fully Extended (lbs.)  | 250               |
| Capacity at 78-1/4" Fully Retracted (lbs.) | 1,500             |
| Capacity at 78-1/4" Second Position (lbs.) | 1,200             |
| Capacity at 78-1/4" Third Position (lbs.)  | 1,000             |
| Capacity at 78-1/4" Fully Extended (lbs.)  | 600               |
| Capacity at 94-1/2" Fully Retracted (lbs.) | 1,850             |
| Overall Width (in.)                        | 12                |
| Overall Retracted Length (in.)             | 65-3/8            |
| Overall Height (in.)                       | 70-1/16           |
| Overall Storage Height (in.)               | 73                |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=582>